

Plug-in card block - SKBI 128-B64/B64 - 2268028

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in card block, Number of positions: 128, Pitch: 0 mm, Connection method: Screw connection, Contact surface: Tin

The illustration shows the version SKBI 128-B 32/B 32



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 053956 |
| Weight per Piece (excluding packing) | 615.0 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|---------------|----------|
| Length | 66 mm |
| Height | 162 mm |
| Width | 252.4 mm |
| Pitch | 0 mm |
| Hole diameter | 4.2 mm |

General

| | |
|----------------------------------|---|
| Range of articles | SKBI 128 |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | current values are defined by the connectors used |
| Nominal voltage U_N | voltage values are defined by the connectors used |
| Nominal cross section | 2.5 mm ² |

Plug-in card block - SKBI 128-B64/B64 - 2268028

Technical data

General

| | |
|------------------------|--------|
| Stripping length | 8 mm |
| Screw thread | M3 |
| Tightening torque, min | 0.5 Nm |
| Tightening torque max | 0.6 Nm |
| Number of positions | 128 |

Connection data

| | |
|--|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 4 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260710 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002642 |
| ETIM 5.0 | EC002780 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Plug-in card block - SKBI 128-B64/B64 - 2268028

Approvals

Approvals


Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Plug-in card block - SKBI 128-B64/B64 - 2268028

Dimensioned drawing

